## NSN 5320-01-477-1656

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-477-1656

#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

0.700 inches

## Head Style:

Flush countersunk

#### Width Between Flats:

0.125 inches

#### Shank Diameter:

0.798 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.295 inches and 0.315 inches

#### Lubrication:

Cetyl alcohol

### Grip Length:

0.375 inches

## Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

2500 pounds per square inch

#### **Thread Size:**

10.0 millimeters

#### Shear Strength:

5380 double pounds per square inch

#### Countersink Angle:

100.0 degrees

#### Material:

Steel

#### **Material Specification:**

Ams 6415 assn standard all material responses

#### Surface Treatment:

Cadmium

## Surface Treatment Specification:

Qq-p-416 ty1 cl 2 federal specification single treatment response

## Thread Series Designator:

Unjf

## Shelf Life:

N/a

# NSN 5320-01-477-1656

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

