

View Online at <https://aerobasegroup.com/nsn/5320-01-477-2607>

Fastener Length:

Between 2.480 inches and 2.520 inches

Head Style:

Straight pan

Head Height:

Between 0.045 inches and 0.055 inches

Shank Diameter:

Between 0.1885 inches and 0.1895 inches

Shank Style:

Pin rivet, threaded

Head Major Diameter:

Between 0.295 inches and 0.315 inches

Grip Length:

Between 2.120 inches and 2.130 inches

Product Name:

Protruding shear head alloy steel 1/16 in. Grip variation

Special Features:

Thread 10-32unjf-3a modified; socket hex. 0.0791 min 0.0808 max, depth 0.115 min 0.135 max, dia. 0.104 min 0.119 max; double shear pounds min. 5, 380; tension pounds min. 2, 500; head chamfer 1/32 in. X 45 deg

Material:

Steel

Material Specification:

Mil-s-5000 military standard 1st material response or mil-s-5626 military standard 2nd material response or mil-s-6049 military standard 3rd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 type ii class 2 color bronze and cetyl alcohol lube per hi-shear specification 305 federal specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.