

View Online at <https://aerobasegroup.com/nsn/5320-01-477-2607>

**Fastener Length:**

Between 2.480 inches and 2.520 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.045 inches and 0.055 inches

**Shank Diameter:**

Between 0.1885 inches and 0.1895 inches

**Shank Style:**

Pin rivet, threaded

**Head Major Diameter:**

Between 0.295 inches and 0.315 inches

**Grip Length:**

Between 2.120 inches and 2.130 inches

**Product Name:**

Protruding shear head alloy steel 1/16 in. Grip variation

**Special Features:**

Thread 10-32unjf-3a modified; socket hex. 0.0791 min 0.0808 max, depth 0.115 min 0.135 max, dia. 0.104 min 0.119 max; double shear pounds min. 5, 380; tension pounds min. 2, 500; head chamfer 1/32 in. X 45 deg

**Material:**

Steel

**Material Specification:**

Mil-s-5000 military standard 1st material response or mil-s-5626 military standard 2nd material response or mil-s-6049 military standard 3rd material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416 type ii class 2 color bronze and cetyl alcohol lube per hi-shear specification 305 federal specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0

**Mil-std (military Standard):**

Mil-s-5000 spec.