
## NSN 5320-01-477-5597

Pin-rivet - Page 1 of 2





## Thread Class:

3a

**Thread Direction:** 

Right-hand

## Fastener Length:

Between 1.740 inches and 1.760 inches

## Head Style:

Straight pan

### Head Height:

0.078 inches

## Width Between Flats:

Between 0.160 inches and 0.180 inches

## Shank Diameter:

0.312 inches

## Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

0.505 inches

#### Lubrication:

Solid film and cetyl alcohol

#### **End Application:**

Structural section, I.H. Inner wing assembly for f-18 e 22-35, f 19-34 aircraft only

#### Grip Length:

Between 1.245 inches and 1.255 inches

#### Thready Qty Per Inch (tpi):

24

#### Thread Size:

0.312 inches

#### **Criticality Code Justification:**

Agav

#### **Product Name:**

(inavy) pin - rivet, threaded, shear, protruding head, hex point drive

#### Material:

Stainless steel

#### **Material Specification:**

Ams 5629 assn standard single material response

#### Surface Treatment:

Passivate

#### Surface Treatment Specification:

Ams-qq-p-35 assn standard single treatment response

#### **Thread Series Designator:**

Unjf

# NSN 5320-01-477-5597

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

