

View Online at <https://aerobasegroup.com/nsn/5320-01-477-5600>

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.740 inches and 1.760 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.068 inches and 0.078 inches

**Width Between Flats:**

Between 0.127 inches and 0.129 inches

**Shank Diameter:**

Between 0.311 inches and 0.312 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.475 inches and 0.505 inches

**Lubrication:**

Solid film or dry film and cetyl alcohol

**End Application:**

Structural section - outer wing assembly, f/a-18e/f aircraft

**Grip Length:**

1.250 inches

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.312 inches

**Criticality Code Justification:**

Agav

**Product Name:**

(inavy) pin - rivet, threaded, shear, protruding head, hex point drive, for sealant application

**Material:**

Stainless steel

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0