## NSN 5320-01-477-5601

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-477-5601

Thread Class:
3a

Thread Direction:
Right-hand
Fastener Length:

Between 1.115 inches and 1.135 inches

Head Style:

Straight pan

Head Height:

0.068 inches
Width Between Flats:

Between 0.127 inches and 0.129 inches

Shank Diameter:

Between 0.311 inches and 0.312 inches

**Shank Style:** 

Pin-rivet, straight, threaded

**Head Major Diameter:** 

Between 0.475 inches and 0.505 inches

Lubrication:

Solid film or dry film and cetyl alcohol

**End Application:** 

Structural section outer wing assembly, f/a-18 e/f aircraft

**Grip Length:** 

0.625 inches

Thready Qty Per Inch (tpi):

24

**Thread Size:** 

0.312 inches

**Criticality Code Justification:** 

Agav

**Product Name:** 

(inavy) pin-rivet, threaded, shear, protruding head, hex point drive, for sealant application

Material:

Stainless steel

**Material Specification:** 

Ams 5629 assn standard single material response

**Surface Treatment:** 

Passivate

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unjf

## NSN 5320-01-477-5601

Pin-rivet - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0