## NSN 5320-01-477-5603

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-477-5603

View Online at https://aerobasegroup.com/nsn/5320-01-477-5603
Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 0.990 inches and 1.010 inches
Head Style:
Straight pan
Head Height:
Between 0.068 inches and 0.078 inches
Width Between Flats:
Between 0.127 inches and 0.129 inches
Shank Diameter:
Between 0.311 inches and 0.312 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.475 inches and 0.505 inches
Lubrication:
Solid film or dry film and cetyl alcohol
End Application:
F/a-18 e/f aircraft
Grip Length:
0.500 inches
Thready Qty Per Inch (tpi):
24
Thread Size:
0.312 inches
Criticality Code Justification:
Agav
Product Name:
(inavy) pin - rivet, threaded, shear, protruding head, hex point drive, for sealant application
Material:
Stainless steel
Material Specification:
Ams 5629 assn standard single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unif

Unjf

## NSN 5320-01-477-5603

Pin-rivet - Page 2 of 2



_						
C	he	14		iŧ	0	•
J			_		ㄷ	-

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0