## NSN 5320-01-477-5632

Pin-rivet - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5320-01-477-5632 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.802 inches and 0.822 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.127 inches and 0.129 inches **Shank Diameter:** Between 0.311 inches and 0.312 inches **Head Major Diameter:** Between 0.597 inches and 0.604 inches Lubrication: Solid film or dry film and cetyl alcohol **End Application:** F/a-18 e/f aircraft **Grip Length:** 0.312 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.312 inches **Countersink Angle:** 100.0 degrees **Criticality Code Justification: Product Name:** (inavy) pin-rivet, threaded, tension 100 degree c'sunk head, hex point drive Material: Stainless steel **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

## NSN 5320-01-477-5632

Pin-rivet - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0