## NSN 5320-01-477-5637

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-477-5637 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.473 inches and 1.493 inches **Head Style:** Err-090 Width Between Flats: Between 0.158 inches and 0.162 inches **Shank Diameter:** Between 0.3740 inches and 0.3745 inches **Head Major Diameter:** Between 0.756 inches and 0.760 inches Lubrication: Solid film and cetyl alcohol, specification 305, hi-shear corp **End Application:** F18 e/f **Grip Length:** Between 0.933 inches and 0.943 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Countersink Angle:** 100.0 degrees **Criticality Code Justification: Product Name:** Pin, rivet, threaded-tension, 100 degree c sunk head, hex point drive Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

N/a

Shelf Life:

## NSN 5320-01-477-5637

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0