NSN 5320-01-477-5638



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-477-5638 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.678 inches and 1.698 inches **Head Style:** Err-090 Width Between Flats: Between 0.160 inches and 0.180 inches **Shank Diameter:** Between 0.302 inches and 0.306 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.597 inches and 0.604 inches Lubrication: Solid film and cetyl alcohol, specification 305, hi-shear corp **End Application:** F18 e/f **Grip Length:** Between 1.183 inches and 1.193 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.3125 inches **Countersink Angle:** 100.0 degrees **Criticality Code Justification:** Agav **Product Name:** Pin, rivet, threaded-tension, 100 degree c sunk head, hex point drive Material: Steel comp xm-13 **Material Specification:**

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

NSN 5320-01-477-5638

Pin-rivet - Page 2 of 2



_						
C	he	14		iŧ	0	•
J			_		ㄷ	-

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0