NSN 5320-01-477-5640

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-477-5640 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.535 inches and 1.555 inches **Head Style:** Err-090 Width Between Flats: Between 0.158 inches and 0.162 inches **Shank Diameter:** Between 0.3740 inches and 0.3745 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.756 inches and 0.760 inches Lubrication: Solid film and cetyl alcohol, specification 305, hi-shear corp **End Application:** F18 e/f **Grip Length:** Between 0.995 inches and 1.005 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Countersink Angle:** 100.0 degrees **Criticality Code Justification:** Agav **Product Name:** Pin, rivet, threaded-tension, 100 degree c sunk head, hex point drive Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate**

Surface Treatment Specification: Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

NSN 5320-01-477-5640

Pin-rivet - Page 2 of 2



| _ | | | | |
|---|----|------|---|------|
| c | hο | JIF. | | ife: |
| J | | | _ | HG. |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0