## NSN 5320-01-477-5641



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-477-5641 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.910 inches and 0.930 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.158 inches and 0.161 inches **Shank Diameter:** 0.374 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.724 inches and 0.731 inches Lubrication: Solid film and cetyl alcohol **End Application:** F/a-18 e/f aircraft **Grip Length:** 0.375 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.375 inches **Countersink Angle:** 100.0 degrees **Criticality Code Justification:** Agav **Product Name:** (inavy) pin-rivet, threaded-tension, 100 degree c'sunk head, hex point drive Material: Stainless steel

**Material Specification:** 

Ams 5629 assn standard single material response

**Surface Treatment:** 

Passivate

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unjf

## NSN 5320-01-477-5641

Pin-rivet - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0