## NSN 5320-01-477-5642



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-477-5642 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.910 inches and 0.930 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.158 inches and 0.161 inches **Shank Diameter:** 0.374 inches **Head Major Diameter:** Between 0.724 inches and 0.734 inches Lubrication: Solid film and cetyl alcohol **End Application:** F/a-18 e/f aircraft **Grip Length:** 0.375 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.375 inches **Countersink Angle:** 100.0 degrees **Criticality Code Justification: Product Name:** (inavy) pin-rivet, threaded-tension, 100 degree c'sunk head, hex point drive Material: Stainless steel **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

## NSN 5320-01-477-5642

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0