

View Online at <https://aerobasegroup.com/nsn/5320-01-477-5643>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.910 inches and 0.930 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.158 inches and 0.161 inches

**Shank Diameter:**

0.374 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.724 inches and 0.731 inches

**Lubrication:**

Solid film and cetyl alcohol

**End Application:**

F/a-18 e/f aircraft

**Grip Length:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.375 inches

**Countersink Angle:**

100.0 degrees

**Criticality Code Justification:**

Agav

**Product Name:**

(inavy) pin-riquet, threaded-tension, 100 degree c'sunk head, hex point drive

**Material:**

Stainless steel

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0