## NSN 5320-01-477-5722

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-477-5722 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.115 inches and 1.135 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.127 inches and 0.129 inches **Shank Diameter:** Between 0.311 inches and 0.312 inches **Head Major Diameter:** Between 0.629 inches and 0.633 inches **End Application:** Fighter aircraft f18 **Grip Length:** 0.625 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.312 inches **Countersink Angle:** 100.0 degrees **Criticality Code Justification:** Agav **Product Name:** Pin, rivet, threaded-tension, 100 degree countersunk head, hex point drive, 125 ksi fsu, nonmagnetic corrosion resistant material **Special Features:** For use with st3m525 and st3m526 collars Material: Nickel alloy 718 **Material Specification:** Ams5662 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5320-01-477-5722

Pin-rivet - Page 2 of 2



Fiig:

A528u0