NSN 5320-01-477-5726

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-477-5726 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.285 inches and 1.305 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.158 inches and 0.161 inches **Shank Diameter:** Between 0.374 inches and 0.375 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.756 inches and 0.760 inches **End Application:** Fighter aircraft f18 **Grip Length:** 0.750 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.375 inches **Countersink Angle:** 100.0 degrees **Criticality Code Justification: Product Name:** Pin, rivet, threaded-tension, 100 degree countersunk head, hex point drive, 125 ksi fsu, nonmagnetic corrosion resistant material **Special Features:** For use with st3m525 and st3m526 collars Material: Nickel alloy 718 **Material Specification:** Ams5662 assn standard single material response **Thread Series Designator:** Unjf Shelf Life:

--

N/a

Unit Of Measure:

NSN 5320-01-477-5726

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0