## NSN 5320-01-477-5779

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-477-5779 **Thread Class:** За Fastener Length: Between 1.427 inches and 1.447 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.160 inches and 0.180 inches **Shank Diameter:** Between 0.311 inches and 0.312 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.597 inches and 0.604 inches **End Application:** Fighter aircraft-first (f18 e/f) **Grip Length:** 0.688 inches Thready Qty Per Inch (tpi): **Countersink Angle:** 100.0 degrees **Criticality Code Justification:** Agav **Special Features:** Distance between the head and injection port is .30 inches.Indented slots on the head are in line with the injection port. Material: Stainless steel **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5320-01-477-5779

Pin-rivet - Page 2 of 2



Fiig:

A528u0