## NSN 5320-01-477-5781

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-477-5781



## Thread Class:

3a

## Fastener Length:

Between 1.427 inches and 1.447 inches

## Head Style:

Flush countersunk

## Width Between Flats:

Between 0.160 inches and 0.180 inches

#### Shank Diameter:

Between 0.311 inches and 0.312 inches

#### Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

Between 0.597 inches and 0.604 inches

#### End Application:

Fighter aircraft-first (f18 e/f)

## Grip Length:

0.688 inches

## Thready Qty Per Inch (tpi):

24

## **Countersink Angle:**

100.0 degrees

## Criticality Code Justification:

Agav

## **Special Features:**

Distance between the head and injection port is .43 inches.Indented slots on the head are in line with the injection port.

## Material:

Stainless steel

## **Material Specification:**

Ams5629 assn standard single material response

## Surface Treatment:

Passivate

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## **Thread Series Designator:**

Unjf

Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-01-477-5781

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

