NSN 5320-01-477-5804

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-477-5804

view Online at https://aeiobasegioup.com/nsn/3520-01-4/7-5004
Thread Class:
3a
Fastener Length:
Between 1.427 inches and 1.447 inches
Head Style:
Flush countersunk
Width Between Flats:
Between 0.160 inches and 0.180 inches
Shank Diameter:
Between 0.311 inches and 0.312 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.597 inches and 0.604 inches
End Application:
Fighter aircraft-first (f18 e/f)
Grip Length:
0.937 inches
Thready Qty Per Inch (tpi):
24
Countersink Angle:
100.0 degrees
Criticality Code Justification:
Agav
Special Features:
Distance from the head to the injection port is .40 inches.Indented slots on the head are in line with the injection port.
Material:
Stainless steel
Material Specification:
Ams5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5320-01-477-5804

Pin-rivet - Page 2 of 2

Fiig: A528u0

