NSN 5320-01-477-5827

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-477-5827

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

1.420 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.158 inches and 0.162 inches

Shank Diameter:

0.374 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.755 inches and 0.760 inches

Grip Length:

0.875 inches

Thready Qty Per Inch (tpi):

24

Thread Size:

0.375 inches

Countersink Angle:

100.0 degrees

Product Name:

Pin-rivet, thread, tension, 100 degree countersunk head hex point drive, for sealant application.

Special Features:

Distance from the head to the injection port is 0.38 inches. Indented slots on the head are in line with the injection port.

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5320-01-477-5827

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

