

View Online at <https://aerobasegroup.com/nsn/5320-01-477-5829>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

1.357 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.158 inches and 0.162 inches

**Shank Diameter:**

0.374 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.755 inches and 0.760 inches

**Grip Length:**

0.812 inches

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.375 inches

**Countersink Angle:**

100.0 degrees

**Product Name:**

Pin-riquet, thread, tension, 100 degree countersunk head hex point drive, for sealant application.

**Special Features:**

Distance from the head to the injection port is 0.50 inches. Indented slots on the head are in line with the injection port.

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0