# NSN 5320-01-477-5843

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-477-5843



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.365 inches and 1.385 inches

### Head Style:

Err-090

### Width Between Flats:

Between 0.104 inches and 0.119 inches

#### Shank Diameter:

Between 0.1810 inches and 0.1840 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.345 inches and 0.352 inches

#### Lubrication:

Solid film and cetyl alcohol, specification 305, hi-shear corp

### **End Application:**

F18 e/f

## Grip Length:

Between 0.870 inches and 0.880 inches

## Thready Qty Per Inch (tpi):

32

## Thread Size:

0.190 inches

## **Countersink Angle:**

100.0 degrees

# Criticality Code Justification:

Agav

# Product Name:

Pin, rivet, threaded-tension, 100 degree c sunk head, hex point drive

## Material:

Steel comp xm-13

# Material Specification:

Ams 5629 assn standard single material response

## Surface Treatment:

Passivate

# Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

# **Thread Series Designator:**

Unjf

# NSN 5320-01-477-5843

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

