NSN 5320-01-477-5843



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-477-5843 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.365 inches and 1.385 inches **Head Style:** Err-090 Width Between Flats: Between 0.104 inches and 0.119 inches **Shank Diameter:** Between 0.1810 inches and 0.1840 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.345 inches and 0.352 inches Lubrication: Solid film and cetyl alcohol, specification 305, hi-shear corp **End Application:** F18 e/f **Grip Length:** Between 0.870 inches and 0.880 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Countersink Angle:** 100.0 degrees **Criticality Code Justification:** Agav **Product Name:** Pin, rivet, threaded-tension, 100 degree c sunk head, hex point drive Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate**

Thread Series Designator:

Unjf

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

NSN 5320-01-477-5843

Pin-rivet - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0