

View Online at <https://aerobasegroup.com/nsn/5320-01-477-5861>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.885 inches and 0.905 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.059 inches and 0.069 inches

**Width Between Flats:**

Between 0.094 inches and 0.096 inches

**Shank Diameter:**

0.249 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.387 inches and 0.412 inches

**Lubrication:**

Solid film or dry film and cetyl alcohol

**End Application:**

F/a-18 e/f aircraft

**Grip Length:**

0.500 inches

**Thready Qty Per Inch (tpi):**

28

**Thread Size:**

0.250 inches

**Criticality Code Justification:**

Agav

**Product Name:**

(inavy) pin-riquet, threaded, shear, protruding head, hex point drive, for sealant application

**Material:**

Stainless steel

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0