## NSN 5320-01-477-5863

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-477-5863

view Offiline at https://aerobasegroup.com/histi/3320-01-477-3003
Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 0.823 inches and 0.843 inches
Head Style:
Straight pan
Head Height:
Between 0.059 inches and 0.069 inches
Width Between Flats:
Between 0.094 inches and 0.096 inches
Shank Diameter:
0.249 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.387 inches and 0.412 inches
Lubrication:
Solid film or dry film and cetyl alcohol
End Application:
F/a-18 e/f aircraft
Grip Length:
0.438 inches
Thready Qty Per Inch (tpi):
28
Thread Size:
0.250 inches
Criticality Code Justification:
Agav
Product Name:
(inavy) pin-rivet, threaded, shear, protruding head, hex point drive, for sealant application
Material:
Stainless steel
Material Specification:
Ams 5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf

## NSN 5320-01-477-5863

Pin-rivet - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0