## NSN 5320-01-477-5872



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-477-5872 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.885 inches and 0.905 inches **Head Style:** Straight pan **Head Height:** Between 0.059 inches and 0.069 inches Width Between Flats: Between 0.094 inches and 0.096 inches **Shank Diameter:** 0.249 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.387 inches and 0.412 inches Lubrication: Solid film or dry film and cetyl alcohol **End Application:** F/a-18 e/f aircraft **Grip Length:** 0.500 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Criticality Code Justification:** Agav **Product Name:** (inavy) pin-rivet, threaded, shear, protruding head, hex point drive, for sealant application Material: Stainless steel **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate** 

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unjf

## NSN 5320-01-477-5872

Pin-rivet - Page 2 of 2



|  | Life: |
|--|-------|
|  |       |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0