

View Online at <https://aerobasegroup.com/nsn/5320-01-477-6905>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.428 inches and 2.448 inches

Head Style:

Err-090

Head Height:

Between 0.045 inches and 0.055 inches

Width Between Flats:

Between 0.104 inches and 0.119 inches

Shank Diameter:

Between 0.202 inches and 0.203 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.295 inches and 0.315 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 1.933 inches and 1.943 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

2600 pounds per square inch

Thread Size:

0.190 inches

Shear Strength:

6130 double pounds per square inch

Material:

Steel

Material Specification:

Mil-s-5000 military specification all material responses or mil-s-5020 military specification all material responses or mil-s-0010 military specification all material responses

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, typeii, class2 federal specification 2nd treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.