

View Online at <https://aerobasegroup.com/nsn/5320-01-477-7471>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.410 inches and 1.535 inches

**Head Style:**

Flush countersunk

**Shank Diameter:**

Between 0.2005 inches and 0.2025 inches

**Shank Style:**

Pin rivet, threaded

**Head Major Diameter:**

0.386 inches

**Lubrication:**

Cetyl alcohol

**End Application:**

F16; f-16 aircraft

**Grip Length:**

Between 0.563 inches and 0.625 inches

**Thready Qty Per Inch (tpi):**

56

**Thread Size:**

0.1640 inches

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 8740 sleeve

**Material Specification:**

Qq-a-430 federal specification single material response collar

**Surface Treatment:**

Cadmium sleeve and chromate sleeve

**Surface Treatment Specification:**

Qq-p-416, ty ii, cl 2 federal specification single treatment response mandrel

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-8740 spec.