NSN 5320-01-477-9489

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-477-9489 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 3.207 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.947 inches and 0.987 inches **Shank Diameter:** Between 0.248 inches and 0.249 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.502 inches and 0.506 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** Truck, fl (m4k) **Grip Length:** 2.812 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 5820 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 9300 double pounds per square inch **Countersink Angle:** 0.250 degrees **Product Name:** 100 degree flush tension head, titanium Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Thread Series Designator:**

Unjf

Shelf Life:

N/a

NSN 5320-01-477-9489

Pin-rivet - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0