

View Online at <https://aerobasegroup.com/nsn/5320-01-477-9489>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

3.207 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.947 inches and 0.987 inches

**Shank Diameter:**

Between 0.248 inches and 0.249 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.502 inches and 0.506 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**End Application:**

Truck, fl (m4k)

**Grip Length:**

2.812 inches

**Thread Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

5820 pounds per square inch

**Thread Size:**

0.250 inches

**Shear Strength:**

9300 double pounds per square inch

**Countersink Angle:**

0.250 degrees

**Product Name:**

100 degree flush tension head, titanium

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams4928 assn standard single material response or ams4967 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0