# NSN 5320-01-478-1041

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-478-1041

## Fastener Length:

Between 0.740 inches and 0.760 inches

### Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

## Shank Diameter:

Between 0.093 inches and 0.097 inches

### Shank Style:

Straight w/radius chamfered tip

## Head Major Diameter:

Between 0.175 inches and 0.183 inches

## End Application:

Used on fighter aircraft f18 e/f

## Grip Length:

0.704 mils and 0.724 centimeters

## **Countersink Angle:**

Between 99.5 degrees and 100.5 degrees

## Product Name:

Rivet, solid, countersunk 100 percent precision head, aluminum and titanium columbium alloy

#### Material:

Aluminum alloy 2117

#### Material Specification:

Qq-a-430 federal specification single material response

#### Surface Treatment:

Anodize

#### Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A040a0

#### Mil-std (military Standard):

Mil-a-8625 spec.