NSN 5320-01-478-1277

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-478-1277



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.947 inches and 0.967 inches

Head Style:

Straight pan

Head Height:

Between 0.059 inches and 0.069 inches

Width Between Flats:

Between 0.094 inches and 0.096 inches

Shank Diameter:

0.249 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.387 inches and 0.412 inches

Lubrication:

Solid film or dry film and cetyl alcohol

Grip Length:

Between 0.557 inches and 0.567 inches

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Product Name:

(inavy) pin - rivet, threaded, shear, protruding head, hex point drive, for sealant application

Material:

Stainless steel

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5320-01-478-1277

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

