NSN 5320-01-478-2068

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-478-2068

view Offilite at https://aerobasegroup.com/hist//3525-01-4/-0-2000
Fastener Length:
Between 0.490 inches and 0.510 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.155 inches and 0.159 inches
Shank Style:
Straight
Head Major Diameter:
Between 0.282 inches and 0.290 inches
End Application:
Harrier, ecp27or1
Countersink Angle:
Between 95.0 degrees and 105.0 degrees
Product Name:
Rivet, solid, countersunk 100 degree, precision head, alluminum and titanium, columbian alloy
Special Features:
Hrivets may be furnished with plain ends or chamfered ends; the conical surface of the head shall be be concentric with the shank of the
rivet; head cocking angle relative to axis of rivet 1/2 degree max
Material:
Aluminum alloy 2117
Material Specification:
Ams4982 assn standard single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 2, class1, dichromate seal military specification single treatment response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):

Mil-a-8625 spec.