NSN 5320-01-478-6577

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-478-6577 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color: Bronze Head Style:** Err-090 **Head Height:** Between 0.037 inches and 0.047 inches Width Between Flats: Between 0.0791 inches and 0.0801 inches **Shank Diameter:** Between 0.1625 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.242 inches and 0.262 inches Lubrication: Cetyl alcohol **Grip Length:** 0.875 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.164 inches **Shear Strength:** 95000 single pounds per square inch **Special Features:** Modified thread dia. 0.1570 in. to 0.1595 in.; double shear 4010.0 pounds; tension 1940.0 pounds Material: Steel **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response **Thread Series Designator:** Unjc

N/a

Shelf Life:

NSN 5320-01-478-6577

Pin-rivet - Page 2 of 2



| ш | ın | 10 | <i>(</i>)+ | Measure: | |
|---|----|----|-------------|----------|--|
| | | | | | |

--

Demilitarization:

No

Fiig:

A528u0