

View Online at <https://aerobasegroup.com/nsn/5320-01-478-6899>

**Fastener Length:**

Between 2.365 inches and 2.385 inches

**Head Style:**

Universal

**Head Height:**

Between 0.040 inches and 0.050 inches

**Shank Diameter:**

Between 0.093 inches and 0.097 inches

**Shank Style:**

Countersunk (undrilled)

**Head Major Diameter:**

Between 0.178 inches and 0.196 inches

**End Application:**

C130 hercules

**Special Features:**

Tend item elevator trim actuator, screw jack; rivet shall drive cold satisfactorily with full heads free from cracks; uniform quality free from scale, fins, seams clinch or die marks, cold shuts or other injurious effects; heat treat and partially precipitation heat treat at 1650 degrees for 25 min and oil quench; age at 1250 degrees to 1350 degrees for 30 to 90 min to meet shear requirements; air cool; shear strength at room temp 85,000 psi to 95,000 as heat treated; 90,000 psi after driving

**Material:**

Iron alloy 660

**Material Specification:**

Amsa286 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A040a0