

View Online at <https://aerobasegroup.com/nsn/5320-01-478-7074>

Thread Class:

3a

Thread Direction:

Right-hand

Identification Code Color:

Black

Fastener Length:

Between 4.385 inches and 5.405 inches

Head Style:

Err-090

Head Height:

Between 0.077 inches and 0.090 inches

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2485 inches and 0.2495 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.415 inches and 0.440 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

W/s: helicopter, electronic countermeasures, eh-60a; helicopter, black hawk uh-60a

Grip Length:

Between 3.995 inches and 4.005 inches

Min. Tensile Strength (psi):

5820 pounds per square inch

Thread Size:

0.250 inches

Material:

Iron alloy 660

Material Specification:

Ams5731 assn standard single material response or ams5737 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Spec. 294, 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Specification Data:

73197-hl448 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0