## NSN 5320-01-478-8492

Fiig: A528u0



Pin-rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-01-478-8492 **Fastener Length:** 0.936 inches **Head Style:** Flush countersunk Shank Diameter: Between 0.189 inches and 0.190 inches **Shank Style:** Stump **Head Major Diameter:** Between 0.293 inches and 0.305 inches Lubrication: Solid film or dry film and cetyl alcohol **End Application:** Aircraft, hornet f/a-18 **Grip Length:** 0.688 inches **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Pin-rivet, grooved, 100 degrees csunk head, shear lockbolt, stump type, titanium, 95 ksi fsu **Special Features:** 4 locking grooves for 0.188 and 0.250 diameter; end may be cupped or flat; 1, 410 to 2210 tension strength lbs min; collar part number nas 1080-06 or nas1080ag06; procurement specification nas 621; hi-cote 2 solid film lube or dry film lube per as5272 (kal gard fa only) plus cetyl alcohal; dimentions to be met before lubrication; locking grooves may be ground or rolled at the manufacturers option; concentricity, conical surface of head to shank within 0.003 tir Material: Titanium alloy uns r56400 **Material Specification:** Nas621 assn standard single material response Shelf Life: N/a **Unit Of Measure: Demilitarization:** No