

View Online at <https://aerobasegroup.com/nsn/5320-01-478-8842>

**Thread Class:**

3a

**Identification Code Color:**

Bronze and red

**Head Style:**

Err-090

**Head Height:**

Between 0.037 inches and 0.047 inches

**Width Between Flats:**

Between 0.0791 inches and 0.0801 inches

**Shank Diameter:**

Between 0.1625 inches and 0.1635 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.242 inches and 0.262 inches

**Lubrication:**

Cetyl alcohol

**Grip Length:**

0.250 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.138 inches

**Shear Strength:**

95000 single pounds per square inch

**Special Features:**

Pin has modified thread dia. 0.157 in. to 0.605 in. ; double shear 4010.0 pounds ; tension 1940.0 pounds ; collar has dia. Of 0.284 in. to 0.292 in. on one end and is 0.314 in. across flats on hex head at other end; hex shear head torque off is 15-25 inch pounds

**Material:**

Steel body

**Surface Treatment:**

Cadmium body

**Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification single treatment response body

**Thread Series Designator:**

Unjc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-a-8625 spec.