NSN 5320-01-478-9265



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-478-9265 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.947 inches and 0.967 inches **Head Style:** Straight pan **Head Height:** Between 0.059 inches and 0.069 inches Width Between Flats: Between 0.094 inches and 0.096 inches **Shank Diameter:** 0.249 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.387 inches and 0.412 inches Lubrication: Solid film or dry film and cetyl alcohol **Grip Length:** Between 0.557 inches and 0.567 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Product Name:** (inavy) pin - rivet, threaded, shear, protruding head, hex point drive, for sealant application Material: Stainless steel **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

Unit Of Measure:

N/a

NSN 5320-01-478-9265

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0