

View Online at <https://aerobasegroup.com/nsn/5320-01-479-1476>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.690 inches and 0.710 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.104 inches and 0.119 inches

Shank Diameter:

Between 0.181 inches and 0.184 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.3765 inches and 0.3813 inches

Expansion Device:

Threaded stem

End Application:

1520-01-8250; helicopter, attack

Grip Length:

0.375 inches

Thread Size:

0.190 inches

Shear Strength:

5380 double pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Steel comp e4340 body or steel comp 4140 body or steel comp 8740 body

Material Specification:

Mil-s-5000 military specification single material response body or mil-s-5626 military specification single material response body or mil-s-6049 military specification single material response body

Surface Treatment:

Cadmium body

Surface Treatment Specification:

Qq-p-416 federal specification single treatment response body

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.