NSN 5320-01-479-4430

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-479-4430 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.635 inches and 0.655 inches **Head Style:** Err-090 Width Between Flats: Between 0.095 inches and 0.097 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.502 inches and 0.507 inches Lubrication: Solid film and cetyl alcohol, specification 305, hi-shear corp **End Application:** F18 e/f **Grip Length:** Between 0.245 inches and 0.255 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Countersink Angle:** 100.0 degrees **Criticality Code Justification:** Agav **Product Name:** Pin, rivet, threaded-tension, 100 degree c sunk head, hex point drive Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

NSN 5320-01-479-4430

Pin-rivet - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0