## NSN 5320-01-479-5219

Pin-rivet - Page 1 of 2

Shelf Life:

N/a



View Online at https://aerobasegroup.com/nsn/5320-01-479-5219 **Thread Class:** 2a **Thread Direction:** Right-hand Fastener Length: 0.638 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.079 inches and 0.080 inches **Shank Diameter:** Between 0.202 inches and 0.203 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.377 inches and 0.381 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** Aircraft, b-1b **Grip Length:** 0.313 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 6130 double pounds per square inch **Countersink Angle:** 100.0 degrees **Product Name:** 100 degree flush ms24894 tension head, titanium Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Thread Series Designator:** Unjf

## NSN 5320-01-479-5219

Pin-rivet - Page 2 of 2



|   | 1  | :. | ~  | 84  |    |    |      |   |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A528u0