NSN 5320-01-479-9178

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Thread Direction:

Fastener Length:

3a

View Online at https://aerobasegroup.com/nsn/5320-01-479-9178



Between 0.577 inches and 0.590 inches Head Style: Countersunk w/reverse chamfer **Head Height:** Between 0.077 inches and 0.090 inches Shank Style: Pin-rivet, tapered, threaded Head Major Diameter: Between 0.415 inches and 0.440 inches **Tip Diameter:** Between 0.241 inches and 0.244 inches **Expansion Device:** Drive stem-type h Lubrication: Cetyl alcohol, specification 305, hi-shear corp Grip Length: 0.500 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Countersink Angle:** 100.0 degrees **Shear Breaking Strength:** 9300 double any acceptable of standard range **Special Features:** Between major diameter: 0.2486 in. And 0.2495 in. Material: Steel comp 303se collar **Material Specification:** Astma-582 assn standard 2nd material response collar Surface Treatment: Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, class2 federal specification single treatment response

Thread Series Designator:

Unjf

NSN 5320-01-479-9178

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6526 spec.

