NSN 5320-01-479-9178

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-479-9178

violi Onimio at https://acrossacogroup.com/noi/20220 01 170 0170
Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 0.577 inches and 0.590 inches
Head Style:
Countersunk w/reverse chamfer
Head Height:
Between 0.077 inches and 0.090 inches
Shank Style:
Pin-rivet, tapered, threaded
Head Major Diameter:
Between 0.415 inches and 0.440 inches
Tip Diameter:
Between 0.241 inches and 0.244 inches
Expansion Device:
Drive stem-type h
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
0.500 inches
Thready Qty Per Inch (tpi):
28
Thread Size:
0.250 inches
Countersink Angle:
100.0 degrees
Shear Breaking Strength:
9300 double any acceptable of standard range
Special Features:
Between major diameter: 0.2486 in. And 0.2495 in.
Material:
Steel comp 303se collar
Material Specification:
Astma-582 assn standard 2nd material response collar
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 1, class2 federal specification single treatment response
Thread Series Designator:
Unif

Unjf

NSN 5320-01-479-9178

Pin-rivet - Page 2 of 2



N/a
Unit Of Measure:
B

Shelf Life:

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6526 spec.