

View Online at <https://aerobasegroup.com/nsn/5320-01-479-9178>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.577 inches and 0.590 inches

Head Style:

Countersunk w/reverse chamfer

Head Height:

Between 0.077 inches and 0.090 inches

Shank Style:

Pin-rivet, tapered, threaded

Head Major Diameter:

Between 0.415 inches and 0.440 inches

Tip Diameter:

Between 0.241 inches and 0.244 inches

Expansion Device:

Drive stem-type h

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

0.500 inches

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Countersink Angle:

100.0 degrees

Shear Breaking Strength:

9300 double any acceptable of standard range

Special Features:

Between major diameter: 0.2486 in. And 0.2495 in.

Material:

Steel comp 303se collar

Material Specification:

Astma-582 assn standard 2nd material response collar

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, class2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6526 spec.