

View Online at <https://aerobasegroup.com/nsn/5320-01-480-4993>

**Thread Class:**

3a

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.197 inches and 0.217 inches

**Shank Diameter:**

Between 0.3740 inches and 0.3745 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.7556 inches and 0.7604 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**End Application:**

Horizontal stablizer, f18/e-f

**Grip Length:**

0.545 inches

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.375 inches

**Countersink Angle:**

100.0 degrees

**Criticality Code Justification:**

Agav

**Product Name:**

Pin, rivet, threaded

**Special Features:**

Threaded-tension; hex point drive

**Material:**

Stainless steel

**Material Specification:**

23-114 mfr ref single material response or ams5629 national specification all material responses

**Surface Treatment:**

Paint head

**Surface Treatment Specification:**

Fed-std-595 federal standard single treatment response head

**Thread Series Designator:**

Unjf

**Specification Data:**

76301-st3-760 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0