

View Online at <https://aerobasegroup.com/nsn/5320-01-480-4993>

Thread Class:

3a

Head Style:

Flush countersunk

Width Between Flats:

Between 0.197 inches and 0.217 inches

Shank Diameter:

Between 0.3740 inches and 0.3745 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.7556 inches and 0.7604 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

Horizontal stablizer, f18/e-f

Grip Length:

0.545 inches

Thready Qty Per Inch (tpi):

24

Thread Size:

0.375 inches

Countersink Angle:

100.0 degrees

Criticality Code Justification:

Agav

Product Name:

Pin, rivet, threaded

Special Features:

Threaded-tension; hex point drive

Material:

Stainless steel

Material Specification:

23-114 mfr ref single material response or ams5629 national specification all material responses

Surface Treatment:

Paint head

Surface Treatment Specification:

Fed-std-595 federal standard single treatment response head

Thread Series Designator:

Unjf

Specification Data:

76301-st3-760 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0