NSN 5320-01-480-5006

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-480-5006

View Online at https://aerobasegroup.com/nsn/5320-01-480-5006
Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 1.103 inches and 1.118 inches
Head Style:
Err-090
Width Between Flats:
Between 0.158 inches and 0.162 inches
Shank Diameter:
Between 0.3740 inches and 0.3745 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.756 inches and 0.760 inches
Lubrication:
Solid film and cetyl alcohol, specification 305, hi-shear corp
End Application:
F18 e/f
Grip Length:
Between 0.558 inches and 0.568 inches
Thready Qty Per Inch (tpi):
32
Thread Size:
0.190 inches
Countersink Angle:
100.0 degrees
Criticality Code Justification:
Agav
Product Name:
Pin, rivet, threaded-tension, 100 degree c sunk head, hex point drive
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:

Unjf

NSN 5320-01-480-5006

Pin-rivet - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0