# NSN 5320-01-480-7028

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-480-7028



#### Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.5725 inches and 0.5925 inches

#### Head Style:

Err-090

#### **Head Height:**

Between 0.080 inches and 0.090 inches

#### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2490 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.415 inches and 0.440 inches

#### **End Application:**

C-17a

## Grip Length:

Between 0.1825 inches and 0.1925 inches

#### Thready Qty Per Inch (tpi):

28

#### **Thread Size:**

0.250 inches

#### Material:

Titanium alloy uns r56400

#### **Material Specification:**

Ams 4967 assn standard single material response or ams 4928 assn standard single material response

#### Surface Treatment:

Aluminum

#### Surface Treatment Specification:

Per hi-shear specification no. 294 mfr ref single treatment response

#### Thread Series Designator:

Unjf

# Shelf Life:

N/a

### Unit Of Measure:

--

### Demilitarization:

No

# NSN 5320-01-480-7028

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

