

View Online at <https://aerobasegroup.com/nsn/5320-01-481-0750>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.552 inches and 1.572 inches

Head Style:

Err-090

Head Height:

Between 0.098 inches and 0.112 inches

Shank Diameter:

Between 0.3422 inches and 0.3432 inches

Shank Style:

Pin-rivet, tapered, threaded

Head Major Diameter:

Between 0.490 inches and 0.520 inches

Tip Diameter:

Between 0.3020 inches and 0.3060 inches

Grip Length:

1.067 inches

Thready Qty Per Inch (tpi):

24

Thread Size:

0.312 inches

Product Name:

Hi-lok pin

Special Features:

Protruding tension head; alloy stel; 1/16 in. Grip variation; 1/32 in. Oversize

Material:

Steel comp 8740 or steel comp 4140 or steel comp e4340

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response

Surface Treatment:

Cadmium

Thread Series Designator:

Unjf

Specification Data:

73197-hl220pb-10-17 professional/industrial association specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.